

# T14



Also available in  
Cold Store Version -30°C



Speed Selector  
to operate with the tiller  
in the upright position



The little helper  
for a big earning of time



High Frequency Batteries charger built-in  
with charge battery indicator

**Pegasolift** 

CE

# T14 SERIES

DIMENSIONS SCHEME		GENERAL SPECIFICATIONS		
	MODEL	T14		
	Load capacity (Q)	1400 kg		
	Weight without load and with lead batteries	220 kg		
	Front rollers truck	460		
	Rear balance wheel truck	545		
	Front rollers size	poliurethane	n° 2 rollers ø 80 × 70	
	Drive wheel size	poliurethane	ø 245×76	
	Balance wheels size	poliurethane	ø 100 × 40	
	Travel speed	with load	4,2 km/h	
		without load	5,1 km/h	
	Lifting speed	with load	0,072 m/s	
		without load	0,110 m/s	
	Lowering speed	with load	0,380 m/s	
		without load	0,110 m/s	
	Max Gradeability	with load	5,0%	
without load		10,0%		
Brake	Electromagnetic			
Electronic control type	Mosfet 24V 110A			
Traction motor power	permanent magnets	700W		
Pump power motor	800W			
Battery charger built-in	High Frequency 24V 10A			
Noise	65 dB			
<b>BATTERIES AVAILABLE</b>				
n° 2 traction acid batteries 12V - 105Ah			57 kg	
n° 2 traction GEL batteries 12V - 100Ah			57 kg	

## The high-efficiency and compact help



**T14 is the need's answer to goods enliven in extra small spaces. Its very compact measures permits to T14 to manoeuvre in a simple and agile way permitting a real time and money saving also to the non-professional utilizer.**

[www.pegasolift.com](http://www.pegasolift.com)

**Pegasolift**

Via del Lavoro 14 - 37047 San Bonifacio (Verona - Italy)  
Tel. (0039) 045/7665570 - Fax: (0039) 045/7665698  
[www.pegasolift.com](http://www.pegasolift.com)



All the pallet trucks of T14 series are manufactured according to the EEC Directive 98/37/CE